UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/594,021	04/24/2007	Heiko Pelzer	AT040015US1	7076
65913 NXP, B.V.	7590 03/17/201	0	EXAM	IINER
NXP INTELLECTUAL PROPERTY & LICENSING M/S41-SJ			HU, JENNIFER F	
1109 MCKAY	DRIVE		ART UNIT	PAPER NUMBER
SAN JOSE, CA 95131		2821		
			NOTIFICATION DATE	DELIVERY MODE
			03/17/2010	ELECTRONIC

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Notice of the Office communication was sent electronically on above-indicated "Notification Date" to the following e-mail address(es):

ip.department.us@nxp.com

	Application No.	Applicant(s)
	10/594,021	PELZER, HEIKO
Office Action Summary	Examiner	Art Unit
	JENNIFER F. HU	2821
The MAILING DATE of this communication ap Period for Reply	opears on the cover sheet with th	e correspondence address
A SHORTENED STATUTORY PERIOD FOR REPL WHICHEVER IS LONGER, FROM THE MAILING ID. - Extensions of time may be available under the provisions of 37 CFR 1 after SIX (6) MONTHS from the mailing date of this communication. - If NO period for reply is specified above, the maximum statutory period. - Failure to reply within the set or extended period for reply will, by statu Any reply received by the Office later than three months after the mailing earned patent term adjustment. See 37 CFR 1.704(b).	DATE OF THIS COMMUNICATION 136(a). In no event, however, may a reply but will apply and will expire SIX (6) MONTHS for the cause the application to become ABANDO	ON. e timely filed rom the mailing date of this communication. DNED (35 U.S.C. § 133).
Status		
3) Since this application is in condition for allowa	is action is non-final. ance except for formal matters,	•
closed in accordance with the practice under	Ex parte Quayle, 1935 C.D. 11,	453 O.G. 213.
Disposition of Claims		
4) ☐ Claim(s) 1,3-9,11-15 and 20-25 is/are pendin 4a) Of the above claim(s) is/are withdra 5) ☐ Claim(s) is/are allowed. 6) ☐ Claim(s) 1,3-9,11-15 and 20-25 is/are rejecte 7) ☐ Claim(s) is/are objected to. 8) ☐ Claim(s) are subject to restriction and/	awn from consideration.	
Application Papers		
9) The specification is objected to by the Examin 10) The drawing(s) filed on is/are: a) ac Applicant may not request that any objection to the Replacement drawing sheet(s) including the correct 11) The oath or declaration is objected to by the Examin	ccepted or b) objected to by the drawing(s) be held in abeyance. ction is required if the drawing(s) is	See 37 CFR 1.85(a). objected to. See 37 CFR 1.121(d).
Priority under 35 U.S.C. § 119		
a) Acknowledgment is made of a claim for foreig a) All b) Some * c) None of: 1. Certified copies of the priority documer 2. Certified copies of the priority documer 3. Copies of the certified copies of the priority application from the International Burea * See the attached detailed Office action for a list	nts have been received. nts have been received in Applic ority documents have been rece au (PCT Rule 17.2(a)).	cation No eived in this National Stage
Attachment(s))	4)	ary (PTO-413)

Application/Control Number: 10/594,021 Page 2

Art Unit: 2821

DETAILED ACTION

1. Amendment B received on June 6, 2009 has been entered into the record in accordance with the Request for Continued Examination filed August 6, 2009.

Response to Arguments

Applicant's arguments filed December 16, 2009 have been considered and are persuasive. The current application claims priority of foreign application EP 04101236, which was filed on March 25, 2004. Therefore, the effective filing date of the current application is March 25, 2004, and Nakamura and Thornell-Pers do not constitute prior art. Therefore, the rejections of claims 1, 3-7, 9, and 11-15 under Tsubaki in view of Nakamura are withdrawn. Furthermore, the rejection of claim 1 under Nakamura in view of Thornell-Pers is withdrawn. However, it is noted that in the office action, the rejections under Tsubaki in view of Nakamura and Nakamura in view of Thornell-Pers were provided *in addition* to the prior rejection under 35 U.S.C. 103(a) under Tsubaki alone, as is noted in paragraph 4 in the office action dated September 25, 2009.

Claim Rejections - 35 USC § 103

- 3. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
 - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 4. Claims 1, 3-7, 9, 11-15 are rejected under 35 U.S.C. 103(a) as being unpatentable over Tsubaki (previously presented).

Application/Control Number: 10/594,021

As to claim 1, Tsubaki teaches an antenna configuration for a telecommunication device wherein the antenna configuration comprising

a first resonator structure (13, Fig. 1) and a second resonator structure (14, Fig. 1) and a control electrode (18, Fig. 1) said two resonator structures are capacitive coupled to one another and said control electrode being provided and realized for changing the capacitive coupling between the first resonator structure and the second resonator structure ("a control electrode for providing coupling capacitances between the open end of the first radiation electrode and the control electrode and between the open end of the second radiation electrode and the control electrode," abstract) and wherein the control electrode being contactable from outside the antenna configuration and wherein a switching means (19, Fig. 1) being associated with the control electrode, by means of the switching means (19, Fig. 1) the control electrode being connectable to a reference potential (ground symbol, Fig. 1).

Tsubaki does not explicitly teach that the switching means comprises a variable capacitance diode, but does teach that the switching means may be a diode [0051], and that by turning on and off a switch, and thus by increasing or decreasing capacitances which determine both of two frequencies, the resonance frequency may be changed [0055]. Therefore, it would have been obvious to one of ordinary skill in the art that any type of diode switch, such as a variable capacitance diode or varactor may be used in the invention to accomplish the function of switching resonance frequencies.

As to claim 3, Tsubaki teaches the switching means (19, Fig. 1) being designed to connect the control electrode (18, Fig. 1) to ground (ground symbol, Fig. 1).

Art Unit: 2821

As to claim 4, Tsubaki teaches the antenna configuration being realized by means of a planar inverted F antenna or a shorted patch antenna or a stub antenna (patch 13 is shorted via connecting electrode 15, Fig. 1).

As to claim 5, Tsubaki teaches the antenna configuration comprising a dielectric substrate (11, Fig. 1, [0011]) retaining the first resonator structure (13, Fig. 1) and the second resonator structure (14, Fig. 1), the first resonator structure being connected to a feed line (17, Fig. 1) provided on the dielectric substrate, and the second resonator structure, by means of the dielectric substrate being electrically isolated (by slit s1, Fig. 1) from the first resonator structure and being located adjacent to the first resonator structure being connected to ground (15 and 16, Fig. 1 connect first and second resonator structures to ground, respectively).

As to claim 6, Tsubaki teaches the first resonator structure (13, Fig. 1) and the second resonator structure (14, Fig. 1) are realized by printed structures printed on a surface of the dielectric substrate (11, Fig. 1).

As to claim 7, Tsubaki teaches the first resonator structure and the second resonator structure are at least partially located in the interior of the dielectric substrate (where the interior of the dielectric substrate can be interpreted as the central portion of the top surface, where the first and second resonator structures extend from edges of slit s1 to the edges of the substrate).

As to claim 9, Tsubaki teaches the switching means comprises a PIN diode or a semiconductor switch ("a switch ... may be of any construction...for example, an element such as a diode, a transistor, a field-effect transistor, etc," [0051]).

As to claim 11, Tsubaki teaches a telecommunication device ("communication device," [0001]), comprising an antenna configuration according to claim 1.

Art Unit: 2821

As to claim 12, Tsubaki teaches a method of operating a telecommunication device comprising an antenna configuration according to claim 1, wherein the antenna configuration comprises a control electrode (18, Fig. 1) said control electrode is contacted from outside the antenna configuration and for changing the resonance frequency of the antenna configuration contacting of the control electrode from outside is done by switchably connecting the control electrode to a reference potential (19, Fig. 1).

As to claim 13, Tsubaki teaches the resonance frequency is changed between a first frequency band and a second frequency band ("double resonance is realized by using two antennas, and, by turning on and off a switch connected to a control electrode," [0018]).

As to claim 14, Tsubaki teaches the method substantially as claimed as applied to claim 13 above, but does not teach the resonance frequency is changed between the DCS band and the UMTS band. However, antennas are frequency scaled to operate anywhere desired in a particular design, and the antenna of Tsubaki can easily to tuned to and utilized for the DCS and UMTS frequency bands by one of ordinary skill in the art.

As to claim 15, Tsubaki teaches the resonance frequency is changed within a given frequency band between a first sub-band and a second sub-band ("double resonance...establish a broader bandwidth," [0018] – [0020]).

As to claim 22, Tsubaki in view of Nakamura do not teach the first resonator structure is sinus-shaped or meander shaped. However, meandering shaped resonant elements are well known in the art and beneficial for reducing the physical length of an antenna element while maintaining a desirable electrical length. Therefore, it would have been obvious to one of

Art Unit: 2821

ordinary skill in the art to modify the first resonator element of Tsubaki by forming it in a meander or sinus shaped in order to miniaturize the antenna configuration.

As to claims 23 and 24, Tsubaki in view of Nakamura do not teach the second resonator structure includes a U-shaped or W-shaped resonator structure and a stripe-shaped, sinus-shaped or meander-shaped auxiliary resonator structure, wherein the U-shaped resonator structure and the stripe-shaped auxiliary resonator structure are contacted to one another. However, resonator structures of different shapes are well known in the art and would have been an obvious modification depending on physical space constraints, the desired operating frequency, etc.

5. Claim 8 is rejected under 35 U.S.C. 103(a) as being unpatentable over Tsubaki in view of Adam (previously presented).

As to claim 8, Tsubaki teaches the antenna configuration substantially as claimed as applied to claim 7 above, but does not teach the antenna configuration being manufactured by usage of low temperature cofired ceramic technology (LTCC). However, low temperature cofired ceramic technology is well known in the art, as taught by Adam, and one of ordinary skill in the art would have been motivated to use LTCC as the substrate because the high dielectric constants of LTCC's allow the antenna unit to be further miniaturized. The multi-layering capability also allows composite electrical parameters to be handled within a single substrate, thus simplifying the manufacture of the antenna unit.

6. Claim 20 is rejected under 35 U.S.C. 103(a) as being unpatentable over Tsubaki in view of Hani (US 6,819,290 -- previously presented).

Tsubaki teaches the antenna configuration substantially as claimed as applied to claim 1 above, but does not explicitly teach the variable capacitance diode is configured to enable a

continuous change of the resonance frequency. Hani teaches an antenna configuration comprising a variable capacitance diode for tuning the antenna to different frequencies, wherein variable capacitance diode is configured to enable a continuous change of the resonance frequency of the antenna configuration. It would have been obvious to one of ordinary skill in the art to modify the diode of Tsubaki with a varactor diode, as taught by Hani, to achieve a range of different capacitances and thus a range of different frequencies.

Page 7

7. Claim 21 is rejected under 35 U.S.C. 103(a) as being unpatentable over Tsubaki, further in view of Rowell (WO 01/20718).

Tsubaki in teaches the antenna configuration substantially as claimed as applied to claim 1 above, but does not explicitly teach that the first and second resonator structures are located entirely in the interior of the dielectric substrate.

Rowell teaches an antenna configuration comprising at least two resonator structures (321, 322, 323, Fig. 3a), wherein the resonator structures are located entirely in the interior of the dielectric substrate (310, Fig. 3a).

All the claimed elements of the invention were known in the prior art and one of ordinary skill in the art could have combined these elements as claimed by known methods and with no change in their respective functions, and the combination would have yielded predictable results to one of ordinary skill in the art at the time of the invention.

Application/Control Number: 10/594,021 Page 8

Art Unit: 2821

Conclusion

Any inquiry concerning this communication or earlier communications from the

examiner should be directed to JENNIFER F. HU whose telephone number is (571) 270-3831.

The examiner can normally be reached on Monday-Friday 9:00am - 4:30pm.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's

supervisor, Douglas Owens can be reached on (571) 272-1662. The fax phone number for the

organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent

Application Information Retrieval (PAIR) system. Status information for published applications

may be obtained from either Private PAIR or Public PAIR. Status information for unpublished

applications is available through Private PAIR only. For more information about the PAIR

system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR

system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would

like assistance from a USPTO Customer Service Representative or access to the automated

information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

/JENNIFER F HU/

Examiner, Art Unit 2821

/Douglas W Owens/

Supervisory Patent Examiner, Art Unit 2821

March 13, 2010